

OD Eagle Panel



We Are People Who Care

OD Eagle 

R32 R410A R22

Model			07K	09K	12K
Performance					
Cooling Capacity	Btu/h		7000	9000	12000
Heating Capacity	Btu/h		7000	9000	12000
Net Dimension					
WxHxD	Indoor	mm	700 × 285 × 188	800 × 300 × 198	850 × 300 × 198
	Outdoor	mm	660 × 500 × 265	730 × 545 × 285	730 × 545 × 285
Packing Dimension					
WxHxD	Indoor	mm	770 × 355 × 272	870 × 370 × 282	920 × 370 × 282
	Outdoor	mm	780 × 565 × 345	847 × 615 × 362	847 × 615 × 362
Loading QTY					
Loading QTY	40H		314	242	240

OD Eagle 

R32 R410A R22

Model			18K	24K	30K	36K
Performance						
Cooling Capacity	Btu/h		18000	24000	30000	36000
Heating Capacity	Btu/h		18000	24000	30000	36000
Net Dimension						
WxHxD	Indoor	mm	970 × 315 × 235	1100 × 330 × 235	1250 × 358 × 253	1460 × 278 × 382
	Outdoor	mm	800 × 545 × 315	825 × 655 × 310	900 × 700 × 350	970 × 805 × 395
Packing Dimension						
WxHxD	Indoor	mm	1047 × 385 × 317	1180 × 400 × 317	1340 × 445 × 355	1552 × 477 × 380
	Outdoor	mm	920 × 615 × 392	945 × 725 × 435	1015 × 762 × 425	1105 × 885 × 495
Loading QTY						
Loading QTY	40H		192	154	126	90



Self-diagnosis Function



ABS material



Sleep Mode



Timer



Outdoor



Control